

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	16Ah
Capacity (10-hour rate)	16Ah
Cold Cranking Amps (CCA, SAE J537)	170A
PHCA - 5-second pulse current	520A
HCA	350A
MCA	280A
Reserve capacity	24 mins
Short circuit current (using IEC method)	1800A
Internal resistance at 20°C (using IEC method)	7 mΩ

Dimensions & Weight

183 mm	
76 mm	
163 mm	
168 mm	
7 kg	
	76 mm 163 mm 168 mm

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 19/04/2022 08:59:52 Information correct at time of exporting PDF. Please check website for updates.



Solutions

EnerSys World Headquarters 2366Bernville Road Reading, PA 19605, USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEAEneEH Europe GmbH152Baarerstrasse 18Gat6300Zug,SingSwitzerlandTel:

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780




Terminal Position



Terminal Type M6 Female

Thread





ODS-AGM16L

©2022 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates. Subject to revisions without prior notice. E.&O.E.